



Novocoat DTM Epoxy

Novocoat DTM Epoxy is a surface tolerant, penetrating coating designed to be used without a primer or topcoat to seal concrete or protect metal from atmospheric corrosion. It can easily be applied by brush or roller at 4 to 8 mils over manually prepared surfaces where blasting is not allowed.

Features

- > 100% solids, no VOCs
- > Exceptional wetting characteristics
- > Low stress, highly flexible film
- > Surface tolerant

Uses

- > Primer/sealer
- > Pipe exterior and pipe racks
- > Support columns
- > Tank tops
- > Bolted connections
- > Edge and corner protection



Novocoat SC1100 Primer/Sealer

Novocoat SC1100 Primer/Sealer is a penetrating, moisture-tolerant epoxy primer that seals porous concrete surfaces to prevent outgassing and associated blisters and pinholes. It promotes adhesion to a variety of finish coats. Also available in fast cure formula, Novocoat SC1100 Primer/Sealer FC.

Features

- > No VOCs
- > Exceptional wetting characteristics
- > Low stress, highly flexible film
- > Adheres to damp concrete
- > Green concrete primer (7+ days)

Uses

- > Concrete primer/sealer
- > Binder for Novolite Aggregate
- > Universal binder for trowel applied flooring



ErgonArmor™

Novolite

PERMANENT CONCRETE REPAIR

Have you ever used a concrete repair product that failed after application?

We have. And we know many others who have done the same. That's why we created Novocoat's Novolite, a three-component, easy to use compound for vertical and overhead areas. This leading edge technology was developed at ErgonArmor's world-class technical laboratory, and its simplicity significantly reduces the chance of user error.

Novolite is much stronger than concrete. When used with NovoPrime 1100, it can penetrate into the substrate and provide a remarkable level of adhesion.

Contact your Novocoat sales representative today to learn more.



How to Apply Novolite



1 BRUSH LOOSE MATERIALS FROM SURFACE

Note: maximum thickness is 4"



2 APPLY THE MIXTURE USING A FLOAT OR TROWEL



3 SMOOTH MATERIAL WITH A STEEL TROWEL OR FLOAT

Ordering Information

For additional information, prices, or to place an order, please contact your ErgonArmor sales representative. If you do not know the name of your sales representative, call **877-98ARMOR**.

Mixes and applications of this product present a number of hazards. Read and follow the hazard information, precautions and first aid directions on the individual product labels and safety data sheets before using. While all statements, technical information, and recommendations contained herein are based on information our company believes to be reliable, nothing contained herein shall constitute any warranty, express or implied, with respect to the products and/or services described herein and any such warranties are expressly disclaimed. We recommend that the prospective purchaser or user independently determine the suitability of our product(s) for their intended use. No statement, information or recommendation with respect to our products, whether contained herein or otherwise communicated, shall be legally binding upon us unless expressly set forth in a written agreement between us and the purchaser/user. Please contact ErgonArmor for further information at **877-982-7667** or FAX **601-933-3381**. For all Terms and Conditions of Sale see ergonarmor.com.

CALL 877-98ARMOR | VISIT ERGONARMOR.COM