



## SELECTION & SPECIFICATION DATA

<b>Type</b>	Asphalt Cutback
<b>Description</b>	Blackhawk 5011 Liquid Asphalt Coating is a liquefied asphalt damp proofing compound formulated to be easily applied by roller, brush, or spray equipment. Blackhawk 5011 Liquid Asphalt Coating can be used as a primer on surfaces to receive Blackhawk Pipe Joint Mastic, Hawk-Seal, and Hawk-Wrap, or as a coating. It dries to a tough, durable, and water-detering layer that maintains excellent performance over a wide range of temperatures and conditions. Available in winter and summer grades.
<b>Uses</b>	Coating for Precast concrete: <ul style="list-style-type: none"> <li>• Manholes</li> <li>• Electrical boxes</li> <li>• Burial vaults</li> <li>• Septic tanks</li> <li>• Box culverts</li> <li>• Pipes</li> </ul>
<b>Color</b>	Black
<b>Topcoats</b>	Consult ErgonArmor
<b>Finish</b>	Black
<b>Dry Film Thickness</b>	5 – 20 mils
<b>Solids Content</b>	65% ± 5% by weight
<b>Theoretical Coverage Rate</b>	160 square feet per gallon at 10 wet mils
<b>VOC Value(s)</b>	<350 g/L

## SUBSTRATES & SURFACE PREPARATION

<b>All</b>	All surfaces must be clean and free from debris and loose scale material or anything that may interfere with adhesion or act as a bond breaker with the desired substrate.
------------	--

## MIXING & THINNING

<b>Mixing</b>	No mixing necessary
<b>Thinning</b>	Do not thin

## APPLICATION EQUIPMENT GUIDELINES

<b>Spray Application</b>	Listed below are general equipment guidelines for the application of this product. Job site conditions may require modifications to these guidelines to achieve the desired results.
<b>Airless Spray</b>	Pump size 15:1 or greater
<b>Hose Length</b>	200 ft x 1/2 in ID
<b>Whip Length</b>	15 ft x 1/4 in ID
<b>Brush</b>	Apply with a wide fiber brush in order to create a smooth uniform film.
<b>Roller</b>	Use a low nap phenolic core roller.

## CLEANUP & SAFETY

<b>Cleanup</b>	Mineral spirits
<b>Safety</b>	Mixes and applications of this product present a number of hazards. Read and follow the hazard information, precautions and first aid directions on the individual product labels and safety data sheets before using.
<b>Ventilation</b>	Thorough air circulation must be used during and after application until the product is cured. User should test and monitor exposure levels to ensure all personnel are within safe limits. Consult product SDS for further information.

## PACKAGING, HANDLING & STORAGE

<b>Shelf Life</b>	12 months at 75°F (24°C) When kept at recommended storage conditions and in original unopened containers.
<b>Package Sizes &amp; Shipping Weight</b>	5 gallon pail (4.7 gallons net fill) – 40 lbs gross weight 55 gallon drum (53 gallons net fill) – 445 lbs gross weight
<b>Storage Temperature &amp; Humidity</b>	40°F – 110°F (4°C – 43.3°C) 0 – 100% relative humidity
<b>Storage</b>	Store indoors. This product is not affected by excursions below these published storage temperatures, down to 10°F (-12°C), for a duration of no more than 14 days. Always inspect the product prior to use.

Rev 06/19

### TERMS AND CONDITIONS OF SALE

While statements, technical information and recommendations contained herein are based on information our company believes to be reliable, nothing contained herein shall constitute any warranty, express or implied, with respect to the products and/or services described herein and any such warranties are expressly disclaimed. We recommend that the prospective purchaser or user independently determine the suitability of our product(s) for their intended use. No statement, information or recommendation with respect to our products, whether contained herein or otherwise communicated, shall be legally binding upon us unless expressly set forth in a written agreement between us and the purchaser/user. For all Terms and Conditions of Sale see [ergonarmor.com](http://ergonarmor.com).

